

Compact Dataloggers

Ideal for small applications



Overview

The CR300 and CR310 are multi-purpose, compact, low-cost measurement and control dataloggers that are ideal for small applications requiring long-term, remote monitoring and control. These entry-level dataloggers, with their rich instruction set, can measure most hydrological, meteorological, environmental and industrial sensors. They will concentrate data, making the data available over varied

networks and deliver the data using your preferred protocol. The CR300-series dataloggers also perform automated on-site or remote decision making for control and M2M communications.

The CR310 is longer than the CR300 and includes an integrated 10/100 Ethernet port and removable terminal connectors.

Benefits and Features

- › Setup easily with PC software and USB connectivity
- › Measure with confidence, analog and digital sensors
- › Internet ready—Email, FTP, HTTP/Web, TCP
- › Trust in the Campbell Scientific quality including integral surge and ESD protection
- › Network wirelessly to another node or Internet gateway with integrated radio option
- › Communicate from anywhere when using a cellular or satellite peripheral
- › Charge batteries using the integrated 12 V-battery regulator
- › Measure smart sensors using RS-232 or SDI-12
- › Connect with PakBus, Modbus, DNP3, GOES, and other standard communication protocols
- › Analyze and control with programmability and multiple general purpose I/O
- › Notify with event driven communications and physical outputs
- › Save money and space with the CR310's integrated Ethernet port
- › Wiring made easy through the CR310's removable terminal block

General Specifications

- › **CPU:** ARM Cortex M4, running at 144 MHz
- › **Internal Memory^a:** 30 MB flash for data storage, 80 MB flash for CPU drive / programs, 2 MB flash for operating system
- › **Clock Accuracy:** ± 1 min per month
- › **USB micro B** for direct connection to PC (limited power source during configuration), 2.0 full speed, 12 Mbps
- › **RS-232** for connecting RS-232 modems or serial sensors
- › **10/100 Ethernet RJ45** for LAN connection (CR310 only)
- › **Battery Terminal Pair (-BAT+)** for regulated 12 V power input or rechargeable 12 V VRLA for UPS mode
- › **Charge Terminal Pair (-CHG+)** for 16 to 32 V from dc power converter or 12 or 24 V solar panel (10 W)
- › **Power Consumption @ 12 Vdc:** 1.5 mA (sleep), 5 mA (1 Hz scan with one analog measurement), 23 mA (active processor always on), 32 mA (CR310 Ethernet idle), 51 mA (CR310 Ethernet active)
- › **View EU Declaration of Conformity Document at:**
www.campbellsci.com/cr300 or www.campbellsci.com/cr310

^aInternal memory is for CR300s with serial numbers ≥ 2813 and CR310s



-WIFI Option Specifications

Wireless Local Area Network (WLAN)

- › **Operational Modes:** Client or Access Point
- › **Supported Standards:** IEEE 802.11 b/g/n, IEEE 802.11d/e/i, 802.1X, WEP, WPA/WPA2-Personal and Enterprise
- › **Maximum Possible Over-the-Air Data Rates**
 - 802.11b: up to 11 Mbps
 - 802.11g: up to 54 Mbps
 - 802.11n: up to 72 Mbps
- › **Operating Frequency:** 2.4 GHz, 20 MHz bandwidth
- › **Antenna Connector:** RPSMA
- › **Antenna:** pn 16005 unity gain (0 dBd), 1/2 wave whip, omnidirectional with articulating knuckle joint for vertical or horizontal orientation.
- › **Transmit Power:** 7 to 18 dBm (5 to 63 mW)
- › **Rx Sensitivity:** -97 dBm

Average Additional Current Contribution @ 12 Vdc

- › **Client Mode:** 7 mA idle, 70 mA communicating
- › **Access Point Mode:** 62 mA idle, 65 mA communicating
- › **Sleep (disabled using IPNetPower() or DevConfig setting):** <0.1 mA

Compliance Information

- › **United States FCC ID:** XF6-RS9113SB
- › **Industry Canada (IC):** 8407A-RS9113SB
- › **View EU Declaration of Conformity Document at:** www.campbellsci.com/cr300 or www.campbellsci.com/cr310

Note: The user is responsible for emissions if changing the antenna type or increasing the gain.

-RF407 and -RF412 Options Specifications

Frequency Hopping Spread Spectrum Radios (FHSS)

- › **Transmit**
 - Output Power: 5 to 250 mW, user selectable
 - Frequency
 - ◆ RF407: 902 to 928 MHz (US, Canada)
 - ◆ RF412: 915 to 928 MHz (Australia, New Zealand)
 - Channel Capacity
 - ◆ RF407: Eight 25-channel hop sequences sharing 64 available channels
 - ◆ RF412: Eight 25-channel hop sequences sharing 31 available channels
 - RF Data Rates: 200 kbps
- › **Receive Sensitivity:** -101 dBm
- › **Antenna Connector:** RPSMA (external antenna required; for Campbell Scientific antennas, see www.campbellsci.com/order/cr300 or www.campbellsci.com/order/cr310)

Average Additional Current Contribution @ 12 Vdc

- › **Transmit:** 45 mA
- › **Idle On:** 12 mA
- › **Idle 0.5 s Power Mode:** 4 mA
- › **Idle 1 s Power Mode:** 3 mA
- › **Idle 4 s Power Mode:** 1.5 mA

Compliance Information

- › **-RF407**
 - United States: FCC Part 15.247: MCQ-XB900HP
 - Industry Canada (IC): 1846A-XB900HP
 - Mexico IF: RCPDIXB15-0672-A2
- › **-RF412**
 - ACMA RCM
 - United FCC Part 15.247: MCQ-XB900HP
 - Industry Canada (IC): 1846A-XB900HP

-RF422 Option Specifications

F868 MHz SRD 860 Radio with Listen Before Talk (LBT) and Automatic Frequency Agility (AFA)

- › **Transmit**
 - Output Power: 2 to 25 mW, user selectable
 - Frequency: 863 to 870 MHz (European Union)
 - Channel Capacity: 30 channels (default), software configurable for meeting local regulations; 10 sequences for reducing interference through channel hop
 - RF Data Rates: 10 kbps
- › **Receive Sensitivity:** -106 dBm
- › **Antenna Connector:** RPSMA (external antenna required)

Average Additional Current Contribution @ 12 Vdc

- › **Transmit:** 20 mA
- › **Idle On:** 9.5 mA
- › **Idle 0.5 s Power Mode:** 3.5 mA
- › **Idle 1 s Power Mode:** 2.5 mA
- › **Idle 4 s Power Mode:** 1.5 mA

Compliance Information

- › **View EU Declaration of Conformity Document at:** www.campbellsci.com/cr300 or www.campbellsci.com/cr310



Global Sales & Support Network

A worldwide network of companies to help meet your needs



- Campbell Scientific group companies
- Sales representatives

Australia

Location: Garbutt, QLD Australia
Phone: 61.7.4401.7700
Email: info@campbellsci.com.au
Website: www.campbellsci.com.au

Brazil

Location: São Paulo, SP Brazil
Phone: 11.3732.3399
Email: vendas@campbellsci.com.br
Website: www.campbellsci.com.br

Canada

Location: Edmonton, AB Canada
Phone: 780.454.2505
Email: dataloggers@campbellsci.ca
Website: www.campbellsci.ca

China

Location: Beijing, P. R. China
Phone: 86.10.6561.0080
Email: info@campbellsci.com.cn
Website: www.campbellsci.com

Costa Rica

Location: San Pedro, Costa Rica
Phone: 506.2280.1564
Email: info@campbellsci.cc
Website: www.campbellsci.cc

France

Location: Antony, France
Phone: 0033.0.1.56.45.15.20
Email: info@campbellsci.fr
Website: www.campbellsci.fr

Germany

Location: Bremen, Germany
Phone: 49.0.421.460974.0
Email: info@campbellsci.de
Website: www.campbellsci.de

South Africa

Location: Somerset West, South Africa
Phone: 27.21.8800885
Email: cleroux@csafrica.co.za
Website: www.csafrica.co.za

Southeast Asia

Location: Bangkok, Thailand
Phone: 66.2.719.3399
Email: thitipongc@campbellsci.asia
Website: www.campbellsci.asia

Spain

Location: Barcelona, Spain
Phone: 34.93.2323938
Email: info@campbellsci.es
Website: www.campbellsci.es

UK

Location: Shepshed, Loughborough, UK
Phone: 44.0.1509.601141
Email: sales@campbellsci.co.uk
Website: www.campbellsci.co.uk

USA

Location: Logan, UT USA
Phone: 435.227.9120
Email: info@campbellsci.com
Website: www.campbellsci.com

