



Peristaltic Pump

Model 410

Designed for field use, the reversible flow **Peristaltic Pump** from Solinst is ideal for vapor sampling, groundwater sampling from shallow wells, or surface water sampling. It can be used for vacuum pumping and for pressure delivery of liquids or gases.

The mechanical peristaltic operation uses rotating rollers to depress the silicone tubing, creating a vacuum, which displaces any fluid or gas in the chosen direction. It is effective to depths up to the suction lift limit, which varies with elevation, and can be as much as 10 m or 33 ft. at sea level.

Peristaltic Pump Design

The **Solinst Peristaltic Pump** features a clear pump head that allows quick, convenient inspection of the pump head tubing before and during operation. The pump head cover is easy to remove for cleaning or replacing the tubing. The pump head tubing guides are designed to keep the tubing in place during sampling, no extra tubing clamps required.

The Peristaltic Pump is compact and lightweight. A handle and one convenient control on the top of the pump make it perfect for fieldwork. A convenient LED indicates pump status.

The Solinst Peristaltic Pump has no vents, grates or openings. The metal case is extremely robust and water resistant. This makes the Peristaltic Pump simple to maintain and repair.

Features of the Peristaltic Pump

- Durable, compact, lightweight, and water-resistant design
- Clear pump head for quick and easy tubing inspection and replacement
- 10 amp breaker switch, eliminating the need to replace fuses
- One simple, easy-access control for reversible flow and variable speeds
- Rugged metal case for durability and easy maintenance.
- Option to automatically control pumping based on water level drawdown when connected to a 101D



Model 410 Peristaltic Pump Specifications	
Sampling Depth:	As much as 10 m (33 ft) at sea level
Pump Size:	33 cm x 13 cm x 17 cm (13" x 5" x 6-1/2")
Pump Weight:	3.3 kg (7.2 lbs)
Power Source:	12 volt DC
Power Draw:	3-5 amps max.
Optional 12V Battery Holder Max. Battery Dimensions:	L: 14.9 cm W: 9.6 cm H: 9.1 cm L: 5.9" W: 3.8" H: 3.6"

Power Source & Motor

A 3 m (10 ft.) power cord uses alligator clips to connect to almost any 12 volt DC power source that can supply at least 3-5 amps at maximum draw (such as auto, marine or small gel cell battery). Connect an optional 12V Battery Holder to the Pump and conveniently add a battery right to the assembly. The pump may also be connected directly to your vehicle battery.

The variable speed motor is reversible, has an easy-to-reset circuit breaker (no fuse to replace), and has reverse polarity protection to prevent damage to the pump.



101D Water Level DrawDown Meter and DrawDown Link Cable

Peristaltic Pump Tubing

The standard pump tubing is 5/8" OD (16 mm) medical grade silicone, which attaches easily to 1/2" OD (13 mm) down-hole tubing. An adaptor kit, which allows the use of 3/8" OD (10 mm) tubing, provides lower sampling rates. This tubing attaches easily to 1/4" OD (6 mm) down-hole tubing. An optional stainless steel tubing weight with a 50 mesh filter screen keeps the down-hole tubing straight and sediments out.

To provide high sample integrity, the sample comes in contact only with the tubing. Replacing the tubing between locations avoids the possibility of cross-contamination. To reduce lengthy decontamination procedures, simply dedicate the inexpensive down-hole tubing.



Optional Tubing Weight

Drawdown Mode

When connected to a **Solinst Model 101D Water Level Drawdown Meter**, the pumping process can be automatically controlled based on the water level detected by the 101D. For example, the Peristaltic Pump will stop when a specified drawdown level is reached and pumping will restart once the water level has recovered.

A **Drawdown Link Cable** is available for connecting the two instruments.

Sampling Rates

The **Model 410 Peristaltic Pump** has variable pumping rates, using two different sizes of silicone pump head tubing. With the standard 5/8" OD (16 mm) tubing it delivers 3.2 L/min.

The 3/8" OD (10 mm) tubing adaptor kit allows a sample rate as low as 40 ml/min. This low rate is ideal for low-flow sampling and the filling of small sample bottles.